

**Device for connecting a wheel axle housing with the chassis of a vehicle**

The invention relates to a device for the connection of a wheel axle housing with the chassis of a vehicle comprising

-a stabilizer with

- 5 a rod-shaped torsion element that is mounted such that it can rotate around its lengthwise axis,

two first arms, positioned across said torsion element, said first arms having first end portions that are rigidly attached to corresponding end portions of said torsion element, and two second arms (drop links), whose first end portions are  
10 articulatedly connected with the second end portions of the first arms, such that the arms extend at an angle in relation to the lengthwise axis of the torsion element,

and further comprising

- a spring/suspension element comprising at least one spring/suspension member having a first member that is connected to the wheel axle housing, and a second  
15 member that is connected to the chassis, such that said member are capable of reciprocal resilient movement.

A device of this type is common for vehicles and can be employed with front axles as well as back axles. Hereunder it is known that the torsion element's housing is attached to the wheel axle and that the torsion element runs along this. If the device  
20 is used for example with a back axle, the first arms normally run horizontally backwards from the torsion element, and the second arms extend vertically upwards, such that the second arms' upper end sections are connected with corresponding side portions of the chassis above and behind the wheel axle.

A disadvantage of such a device is that it occupies space in the vehicle behind the  
25 wheel axle and contributes to a greater length of the vehicle. In addition, because of the fact that the heavy torsion element and partly the first arms move together with the wheel axle, the mass of the vehicle not supported by the spring/suspension device will be great, something which negatively affects the vehicle's driving performance.

30 According to the prior art, the spring/suspension element can comprise for example four spring/suspension members that are attached in pairs to two horizontal yokes that are attached to and run crosswise to the wheel axle. These yokes are also heavy and contribute to the mass of the vehicle not supported by the spring/suspension device being great.

35 It is known from the prior art that it is normal for a back axle to be connected to the chassis by a so-called V-rod that maintains the back axle sideways in relation to the

chassis, and two reaction rods that prevent a rotation of the back axle along the vertical axis of the vehicle. If the back axle moves in a vertical direction in relation to the chassis at the same time that the vehicle tilts, the result can be a mutual sideways movement of the end portions of the spring/suspension elements, which  
 5 have resulted in an increased strain on the spring/suspension elements reducing their lifetime.

With vehicles having a plurality of front wheel axels and/or back wheel axels, it is known from the prior art that one or more of these can be lifted such that the corresponding wheel does not touch the ground. To achieve this, there is arranged  
 10 in the chassis a support member or bridge that runs crossways in relation to the length of the vehicle, and that near the midsection of the wheel axle carries a special lifting actuator. The separate bridge and actuator contribute to increasing the weight of the vehicle, the production time and the price.

The object of the invention is to provide a device of the type described above that is  
 15 to a lesser degree affected by the above-described disadvantages.

The characteristic features of the device according to the invention are specified in the claims.

The invention will be described in more detail below with reference to the figures that show embodiments of the device according to the invention.

20 Fig 1 is perspective view of a rear portion of a vehicle, seen from below and from the back, wherein obscuring portions have been omitted.

Fig 2 is a longitudinal section through the device according to the invention, wherein obscuring portions have been omitted.

25 Fig 3 is a longitudinal section similar to that shown in fig 2, but showing a different embodiment of the invention.

In fig 1 and 2 is shown two frame beams 1, 2 of a chassis of a vehicle and a rear axle housing 3, which is located under frame beams 1, 2, wherein these frame beams hereafter shall represent the chassis. Running in front of and over back axle  
 30 housing 3 in the crossways direction of the vehicle is a rod shaped torsion element 4 of a stabilizer 5. Torsion element 4 is arranged in the chassis such that it can rotate along its longitudinal axis 6.

Horizontally and behind torsion element 4 run two first arms 11,12 whose first end portions 13,14 are rigidly attached to corresponding end portions 7, 8 of torsion  
 35 element 4. Second end portions 15,16 of the first arms 11,12 are articulatedly attached with corresponding first end portions 23,24 of two vertically, downwardly

projecting second arms 21,22 (drop links) via shaft extensions 51,52 that extend in the crossways direction of the vehicle, and that are shown only by indicating the longitudinal axis of such shaft extensions. Second end portions 25,26 of the second arms 21,22 are articulately connected with back axle housing 3 via shaft extensions 53,54 that extend in the crossways direction of the vehicle, and that are likewise only shown by indicating the longitudinal axis of such shaft extensions.

The torsion element's end portions 7, 8 are also rigidly connected with corresponding, first end portions 33, 34 of two third arms 31, 32, that preferably extend at an angle downward and forward. Second end portions 35,36 of the third arms 31,32 are articulately connected with two corresponding first end portions 43,44 of two press rods or fourth arms 41,42 of two spring/suspension elements 61,62 via corresponding axels 55, which are shown only by indicating the axle's longitudinal axis.

As shown in fig 2 and 3, press rod's second end portions 45,46 are fixedly attached to a corresponding outer housing 63 of spring elements 61,62. These housings 63 and have a bottom 65 and a cylindrical sidewall 66 and an opening 67 on the opposite side of bottom 65. The fourth arms 41,42 extend through the corresponding openings 67 and are fixedly attached with the portion of bottom 65 directed in towards the interior of housing 63,64.

A piston-like head 68 is slidably and sealingly arranged in outer housing 63 and is introduced in the housing via opening 67. Head 68 is connected to the chassis via a shaft extension 56 that runs parallel with shaft extension 55. Alternatively, axle extension 56 may have a spherical surface that permits the swinging of head 68 also about an axis that runs perpendicular to the longitudinal axis of the fourth arms 41,42. Within head 68 is provided an axial bore 69, where through run the corresponding, fourth arms 41, 42, such arms being sealingly arranged and displaceable in their lengthwise direction in relation to housing 63 i.e. either slidable or with clearing. A seal can be achieved by the help of a membrane 60 that is attached to both housing 63 and head 68, such that a portion of membrane 60 runs along the inside of housing wall 66 and another portion of the membrane runs along the outside of the outer surface of head 68. Between these two portions, the membrane has a folded portion. Membrane 60 defines a first pressure chamber 70.

This embodiment of the device according to the invention functions as described below.

When the chassis exerts a load on wheel axle housing 3, and for the sake of simplicity is assumed that the chassis does not tilt in relation to the wheel axle housing, then the chassis will as a result be lowered in relation to wheel axle housing 3. Thereby, torsion element 4 will be rotated in relation to the chassis, in that the first arms will be swung in a counterclockwise direction as shown in fig 3

because of these arms' connection with wheel axle housing 3 via the second arms 21,22.

Because torsion element 4 is however also connected with the third arms 31,32 and also attempt to rotate these in a counterclockwise direction, then these third arms  
 5 will attempt to draw the fourth arms 41,42 and the housing 63,64 towards the right as shown in fig 3. Because head 68 however is connected with the chassis via axle extension 56, the volume of pressure chamber 70 will be reduced, whereby the pressure of the gas in pressure chamber 70 will be increased and exert a force that attempts to press housings 63 and the arms in the opposite directions. This pressure  
 10 thereby creates an opposing force that prevents a further lowering of the chassis in relation to the wheel axle housing 3.

The vertical arrangement of the second arms 21,22 and the arrangement of the spring/suspension elements 61,62 that are connected to torsion element 4 via the third and the fourth arms 31,32 and 41,42 respectively, creates a minimally space-  
 15 demanding, inexpensive and simple spring/suspension of wheel axle housing 3 in the vehicle. The arrangement of the torsion element and the spring/suspension elements on the side of the wheel axle housing that is directed towards the vehicle's midsection, seen from the vehicle's lengthwise direction, allows for a reduction in the length of the vehicle.

20 In either housing 61,62 or head 68 there can be provided a channel 71 that by way of a valve 72 can be arranged to be connected to a pressurized gas source 73, that in the event of a gas leakage from pressure chamber 70 can be filled with gas. In the alternative, the ground clearance of the vehicle's chassis can be set.

The spring/suspension elements thereby function as a simple pressure fluid actuator.

25 The device can be used in a simple matter for raising of the wheel axle housing. For this purpose, as shown in fig 3, head 68 can for example be provided with an extension of boring 69, wherein this extension is concentric in relation to bore 69 and forms a cylinder 80. The fourth rod 41,42 is hereby provided with a flange that forms a piston 81 that is arranged to sealingly glide in cylinder 80 in that piston 81  
 30 is provided with a gasket 82. Cylinder 80 has a bottom 83 and near bottom 83 the head carries a gasket 84 that creates a seal between the fourth rod 41,42 and boring 69 in head 68. The bottom 83, cylinder 80 and piston 81 defines a second pressure gas chamber 85, and there is arranged in head 68 a channel 86 that is designed to connect chamber 85 with pressurized gas source 73 by way of a valve 87. It should  
 35 be understood that the channel can alternatively be provided in the housing and/or the fourth arm 41.

By the introduction of pressurized gas in the second chamber 85 and the possible release of gas from the first chamber 70, the fourth arms 41,42 can be moved to the

right as shown in fig 4 and the first, second and third arms as well as the torsion element can be swung counterclockwise and the wheel axle housing thereby raised in relation to the chassis until the wheels touch the ground, in that the chassis will then be supported by the remaining wheel axles.

- 5 It can thus be seen that the invention provides a very compact, inexpensive and simple multifunction device for supporting a wheel axle housing in a vehicle.

10

15

20